

CLIENT REFERENCE/PROJECT <i>Cliente/Nome del progetto</i>	Steel mill <i>Acciaieria</i>
PLACE/Luogo	Bangladesh
YEAR/Anno	2022
FLUID/Fluido	Natural gas
PRODUCT USED/Prodotto utilizzato	PRS <i>Gruppo riduzione</i>
DESCRIPTION/Descrizione	<p>PRS capacity 8500 Nm³/h, single line, inlet pressure 6 barg, outlet pressure 0,125 barg, direct operated spring type regulator with OPSO, DN inlet 350, DN outlet 600, rating PN16</p> <p>Separate reducing line for pilot with capacity 20 Nmch.</p> <p>Separate reducing line for nitrogen with capacity 600 Nmch inlet pressure 12 barg, outlet pressure 250 mbar.</p> <p><i>Gruppo riduzione portata 8500 Nm³/h singola linea, pressione ingresso 6 barg, pressione uscita 0,125 barg, riduttori di pressione ad azione diretta con valvola di blocco, DN ingresso 350, DN uscita 600, rating PN16.</i></p> <p><i>A bordo linea di alimentazione piloti portata 20 Nm³h e linea di riduzione azoto portata 600 Nmch pressione ingresso 12 barg e pressione di uscita 250 mbar.</i></p>
STANDARD	2014/68/EU PED



